


→ Series 2782



EAC

■ MATERIAL



■ SPECIFICATION



3/4" – 1"



– 200°C to + 120°C



PN 63

■ SUITABLE FOR

Liquids	neutral and non-neutral	
Air, gases and vapours	neutral and non-neutral	

■ EXAMPLES OF USE

Diverter ball valve for the installation of for example two safety valves in combination with bursting discs for the protection of containers designed for the storage of cryogenic gases. The requirements of the PED relating to redundant or diverse safety devices are fulfilled by this fitting in combination with safety valves of the 2400 / 2480 series. On each side two additional connections for bursting discs are available. In case the safety valves need to be maintained or the bursting discs replaced, the side requiring maintenance can be shut off.

- For the storage of cryogenic liquified gases, such as LIN, LOX, LAr, CO₂, LNG.
- N₂ in pharmaceutical / foodstuffs applications
- O₂ for medical supply equipment
- CO₂ for foodstuffs/ industrial applications
- LAr for welding
- Cooling plants

The ball-valves are oil- and grease-free as standard. For applications with oxygen (O₂) applicable up to maximum 40 bar and 60°C.

■ APPROVALS

TR ZU 010/2011

Anforderungen

AD 2000-Merkblatt A4
DGR 2014/68/EU

■ MATERIAL

Component	Material	DIN EN	ASTM
Body	Gunmetal	CC499K	CC499K
Internal parts	Stainless steel	1.4404	316L
Primary Seal	PTFE mod.	PTFE mod.	PTFE mod.
Secondary Seal	PTFE	PTFE	PTFE

Series 2782 ■ BALL VERSION

B01	L-Bore
B02	T-Bore

■ MEDIUM

GF	gaseous and liquid	cryogenic liquified gases, vapours and liquids
----	--------------------	--

■ TYPE OF OPERATION

A01	cranked handle made of gunmetal
-----	---------------------------------

■ AVAILABLE NOMINAL DIAMETERS AND CONNECTION SIZES

Nominal diameter DN		20	
Inlet		1" (25)	NPT 1" (25)
Outlet	1/2" (15)	■	
	1/2" - 3/4" (15/20)	■	
	1/2" NPT (15)		■
	1/2" NPT (15)- 3/4" NPT (15/20)		■


■ TYPE OF CONNECTION INLET / OUTLET THREADED CONNECTIONS

f / f	Standard	Female thread BSP-P / Female thread BSP-P	DIN EN ISO 228-1 / DIN EN ISO 228-1
NPT-f / NPT-f		Female thread NPT-f / Female thread NPT-f	ANSI B1.20.1 / ANSI B1.20.1

■ NOMINAL DIAMETERS, CONNECTIONS, INSTALLATION DIMENSIONS

Series 2782: Connection, installation dimensions					
Nominal diameter	DN	20			
Connection	Gi	1" (25)	1" (25)	NPT 1" (25)	NPT 1" (25)
Outlet	Got / Gob	1/2" (15)	1/2"-3/4" (15/20)	1/2" NPT (15)	1/2" NPT -3/4" NPT (15/20)
Installation dimensions in mm	Cot	28	33	-	-
	Cob	28	28	-	-
	T1	20	20	20	20
	T2/T3	15	15	15	15
	H1	41	41	41	41
	H2	72	72	72	72
	H3	94	94	94	94
	H4	128	128	128	128
	B1	31	31	31	31
	B2	50	50	50	50
	B3	52	52	52	52
	B4	62	62	62	62
	L1	231	231	231	231
	L2	165	165	165	165
	L3	161	161	161	161
	L4	305	305	305	305
	SW1	9	9	9	9
	SW2	36	36	36	36
	K	30	30	30	30
	G4	M10	M10	M10	M10
	T4	10	10	10	10
Narrowest diameter	d0	16	16/21,5	16	16/21,5
Test port	G1/4	1/4"	1/4"	1/4"	1/4"
Weight	kg	5,9	5,7	5,9	6,1
Kvs-value	m3/h	6,9	6,9 / 12,2	6,9	6,9 / 12,2

■ MAIN DIMENSIONS, INSTALLATION DIMENSIONS



Series 2782 ■ INDIVIDUAL SELECTION / VALVE CONFIGURATION

Series	Ball Version	Medium	Operation	Nominal diameter DN	Connection type		Connection size		Options	Quantity
					Inlet	Outlet	Inlet	Outlet		
2782	B02	GF	A01	20	f	f	20	15		2
2782		GF	A01							
2782		GF	A01							
2782		GF	A01							

■ TECHNICAL FINISHES, VARIANTS, ACCESSORIES										
S75	fitted with lateral overflow valve DN10 to prevent the activation of the safety valves									<input type="checkbox"/>
S76	fitted with lateral overflow valve DN15 to prevent the activation of the safety valves									<input type="checkbox"/>
A15	Diverter ball valve with shut-off device									<input type="checkbox"/>
										<input type="checkbox"/>

■ CERTIFICATES / APPROVALS					
C01	Factory certificate acc. DIN EN 10204 2.2 (WKZ 2.2)	<input type="checkbox"/>	C05	Sealing material manufacturer certification (FDA, USP 3, 3-A...), Please indicate description of certificate: _____	<input type="checkbox"/>
C02	Test certificate acc. DIN EN 10204 3.1 (WPZ 3.1)	<input type="checkbox"/>	C06	ATEX evaluation acc. to 2014/34/EU	<input type="checkbox"/>
C03	Material test certificate acc. DIN EN 10204 3.1 (MPZ 3.1) (pressure retaining part)	<input type="checkbox"/>	C11	Certification of the production process especially for gaseous oxygen applications by employment of specific materials	<input type="checkbox"/>

■ ADMISSIONS / ACCREDITATIONS											
AA4	EAC - certificate/declaration with passport for the valve and laser marking of the valve				<input type="checkbox"/>	AL	Individual inspection by notified body inspector – (body to be indicated):				<input type="checkbox"/>
					<input type="checkbox"/>						<input type="checkbox"/>
					<input type="checkbox"/>						<input type="checkbox"/>

■ ENQUIRY										
Copy and send to: order@goetze.de .										